SBIG ASTRONOMICAL INSTRUMENTS

SANTA BARBARA INSTRUMENT GROUP

147-A Castilian Drive Santa Barbara, CA 93117 Phone (805) 571-SBIG (571-7244) FAX (805) 571-1147 e-mail:sbig@sbig.com home page:www.sbig.com

SBFITSEXT Version 1.0 A Set of FITS Standard Extensions for Amateur Astronomical Processing Software Packages

March 19, 2003

This document describes a set of Extensions to the FITS standard for use with Amateur Astronomical Image Processing (AIP) Software Packages. The current state of uniformity between the major AIP Software Packages is dismal at best. The hope is that in publishing this Standard all the Major Packages (CCDOPS, MaximDl and CCDSoft, etc.) will commit to adhere to this Standard and that will then give the other Packages sufficient reason to adhere.

Mandatory Keywords

The following Keywords are all **mandatory** in the FITS Standard and thus must be included in this Standard:

SIMPLE BITPIX NAXIS NAXIS1 NAXIS2

As these keywords are defined in the FITS standard we won't repeat the keyword types (String, Float, etc.) or default/typical values but instead refer you to the actual FITS standard.

Mandatory Standard Reserved Keywords

These keywords are defined in the FITS Standard and per this Standard are **mandatory**:

OBJECT TELESCOP INSTRUME OBSERVER DATE-OBS	<pre>String - The name of Object Imaged, ie M57 String - The model Telescope, ie LX200 String - The model Camera used, ie ST-7 String - The name of the Observer, ie John Doe String - The UTC date and time at the start of the exposure in the ISO standard 8601 format: '2002-09-07T15:42:17.123' (CCYY-MM-DDTHH:MM:SS.SSS). Note that we have dropped the non-standard but common TIME-OBS keyword by including the time in DATE-OBS.</pre>
BSCALE	Floating Point - The last two are for 16 bit images. Typically
	BSCALE = 1.0
BZERO	Floating Point - Typically 32768.0
HISTORY	String - Include multiple copies of this keyword for every modification made to the image in the order made. The table below lists the common modifications and should be included as stated below. Modifications not included in the list should use language that reasonably describes the modification:

Dark Subtraction
Bias Subtraction
Flat Field
Image Co-Addition
LR Deconvolve Image
DDP Image

Crop Image
Flip Horizontally
Flip Vertically
Rotate Image
Resample Pixel Size
Enlarge Image
Reduce Image

Scale ADU Values
Remove Cool Pixels
Smooth Pixels
Sharpen Pixels
Quantize ADU Values
Remove Warm Pixels
Log Scale ADU Values
Invert ADU Values

Mandatory Extension Keywords

DATAMAX

SWCREATE

SWMODIFY

The following Keywords are not defined in the FITS Standard but are defined in this Standard. **All must be included**.

EXPTIME	Floating Point - The total exposure time in seconds. For Track
	and Accumulate Images this is the sum of all the exposure times.
CCD-TEMP	Floating Point - Temperature of CCD when exposure taken
XPIXSZ	Floating Point - Pixel width in microns (after binning)
YPIXSZ	Floating Point - Pixel height in microns (after binning)
XBINNING	Integer - Binning factor in width
YBINNING	Integer - Binning factor in height
XORGSUBF	Integer - Sub frame X position of upper-left pixel relative to
	whole frame in binned pixel units
YORGSUBF	и и У и
EGAIN	Floating Point - Electronic gain in e-/ADU
FOCALLEN	Floating Point - Focal Length of the Telescope used in
	millimeters
APTDIA	Floating Point - Aperture Diameter of the Telescope used in
	millimeters.
APTAREA	Floating Point - Aperture Area of the Telescope used in square-
APIAREA	Floating Form: - Aperture Area of the refescope used in square-
APIAREA	millimeters. Note that we are specifying the area as well as the
AFIAREA	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central
	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction.
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. **Integer - Upon initial display of this image use this ADU level**
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level.
	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be used:
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be used: Background = CBLACK
CBLACK CWHITE	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be used: Background = CBLACK Range = CWHITE - CBLACK
CBLACK	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be used: Background = CBLACK Range = CWHITE - CBLACK Integer - Add this ADU count to each pixel value to get to a
CBLACK CWHITE	millimeters. Note that we are specifying the area as well as the diameter because we want to be able to correct for any central obstruction. Integer - Upon initial display of this image use this ADU level for the Black level. Integer - Upon initial display of this image use this ADU level as the White level. For the SBIG method of displaying images using Background and Range the following conversions would be used: Background = CBLACK Range = CWHITE - CBLACK

Integer - Pixels at or above DATAMAX are considered to be
saturated and thus unusable for Photometric calculations

initially created this file ie 'SBIGs CCDOps Version 5.10'

String - This indicates the name and version of the Software that

String - This indicates the name and version of the Software that

modified this file ie 'SBIGs CCDOps Version 5.10' and there can be multiple copies of this keyword. Only add this keyword if you

set PEDESTAL to -100 in this case.

actually modified the image and we suggest placing this above the **HISTORY** keywords corresponding to the modifications made to the image.

SBSTDVER String - This string indicates the version of this standard that the image was created to ie 'SBFITSEXT Version 1.0'

Optional Keywords

The following Keywords are not defined in the FITS Standard but are defined in this Standard. They may or may not be included by AIP Software Packages adhering to this Standard. Any of these keywords read by an AIP Package must be preserved in files written.

FILTER	String - Optical Filter used to take image, ie H-Alpha. If this keyword is not included there was no filter used to take the image.
TRAKTIME	Floating Point - If the image was auto-guided this is the exposure time in seconds of the tracker used to acquire this image. If this keyword is not present then the image was unguided or hand guided.
SNAPSHOT	<pre>Integer - Number of images combined to make this image as in Track and Accumulate or Co-Added images.</pre>
SET-TEMP	Floating Point - This is the setpoint of the cooling in degrees C. If it is not specified the setpoint is assumed to be the CCD-TEMP specified above.
IMAGETYP	String - This indicates the type of image and should be one of the following: Light Frame Dark Frame Bias Frame Flat Field
OBJCTRA	String - This is the Right Ascension of the center of the image in hours, minutes and seconds. The format for this is '12 24 23.123' (HH MM SS.SSS)using a space as the separator.
OBJCTDEC	String - This is the Declination of the center of the image in degrees. The format for this is '+25 12 34.111' (SDD MM SS.SSS) using a space as the separator. For the sign, North is + and South is
CENTAZ	String - Azimuth in degrees of the center of the image in degrees. Format is the same as the OBJCTDEC keyword.
CENTALT	String - Altitude in degrees of the center of the image in degrees. Format is the same as the OBJCTDEC keyword.
SITELAT	String - Latitude of the imaging location in degrees. Format is the same as the OBJCTDEC keyword.
SITELONG	String - Longitude of the imaging location in degrees. Format is the same as the OBJCTDEC keyword.

Evolution of the Standard

Over time it is anticipated that this standard will want to evolve. The mechanism for that will be mostly informal. If you have proposed changes or additions to this standard please forward them to:

Matt Longmire SBIG matto@sbig.com

Periodically I'll revise the Standard.